

HAND SINKSwith SOAP and PAPER TOWEL DISPENSER









Includes Skirt



 Item #: ______ Qty #: _____

 Model #: ______

 Project #: ______

Keyhole Bracket for easier installation and greater stability.



FEATURES:

One piece Deep Drawn sink bowl design.

Sink bowl is 10" x 14" x 5".

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

Keyhole wall mount bracket.

Stainless steel basket drain 1-1/2" IPS.

Towel dispenser with hinged towel box. Unit uses standard C-fold towels.

Liquid Soap Dispenser.

Splash mounted 4" O.C. gooseneck faucet furnished with aerator.

Specific Features:

7-PS-69 wrist handle faucet. Side support brackets included.

7-PS-69 & 7-PS-80 lever operated drain and

built-in overflow with plastic overflow tube and spring clamps. P-Trap is 1 1/2".

7-PS-85 chrome plated 1 1/2" P-Trap & apron.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed Countertop Edge with a No-Drip offset.

One sheet of stainless steel- No Seams.

MATERIAL:

Heavy gauge type 304 series stainless steel.

Wall mounting bracket is Galvanized and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

MECHANICAL:

Faucet supply is 1/2" IPS male thread hot and cold.

For A.D.A Compliant Units
with a paper towel dispenser,
please see Model 7-PS-41 on the
A.D.A. Hand Sink Specification Sheet



Standard Faucet conforms to NSF 61 Standard 9. An optional faucet upgrade is required for compliance to AB 1953 Standards.

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at www.advancetabco.com



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

NEW YORK Fax: (631) 242-6900 **GEORGIA** Fax: (770) 775-5625

TEXAS

NEVADA

Fax: (972) 932-4795 Fax: (775) 972-1578

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL



