


Foodservice Equipment • Material Handling, Healthcare & Cleanroom Equipment • Retail Display

1800 Series Underbar Sinks

with Splash Mount Faucet

Item #:	Oty.:	
Model #:	Project #:	
Optional Accessories	Model #	Qty.
Leg & faucet kit		
S/S legs		
Speed rail		





- ◆ 20 gauge, type 304 stainless steel construction.
- ◆ Available in a variety of sizes, from 3´(914mm) to 8´(2438mm) length.
- Models offered with two-, three-, or fourcompartment sinks, all of which are one-piece and deep-drawn.
- Bowls are 10" x 14" x 10" (254 x 356 x 254mm).
- Legs include welded crossbrace front-to-back.
- ◆ 1½ " (38mm) drains with standpipe overflows included.
- ◆ Splash mount faucet with 10" (254mm) spout.
- ◆ 4½" (114mm)- High backsplash.



Spec sheets available for viewing, printing or downloading from our online literature library at www.eaglegrp.com



Foodservice Division: (800) 441-8440 MHC/Retail Display Divisions: (800) 637-5100

FAX: (302) 653-2065 or 653-3036

For custom configuration or fabrication needs, contact our **SpecFAB Division**.


Phone: (302) 653-3000. FAX: (302) 653-3091. E-mail: specfab@eaglegrp.com



Details & Specifications

Profit from the Eagle Advantage

1800 Series Underbar Sinks



side view dimensions of all 1800 Series underbar sinks

model #

B8C-18

B8C-4-18

kg

44.5

47.2

98

104

- Top, front, and ends are 304 series stainless steel construction. Back panels are galvanized steel.
- ◆ 4½" (114mm)-high backsplash.
- ◆ 10" x 14" x 10" (254 x 356 x 254mm) bowls.
- Welded crossbraced galvanized legs.
- ◆ 1½" drain with removable standpipe on sinks.
- Splash mount 4" (102mm) center faucet with 10" (254mm) spout.

Easy order Leg & faucet kits Add suffix "LF" to model #. items included model

305540

313302

___ 25" __ (635mm)

stainless steel legs

T&S faucet

1800 Series underbar sinks 3' (914mm) length weight model # lbs. kg (330mm) (330mm) B3L-2-18 68 30.8 -3´ (914mm) - 3´ (914mm) B3R-2-18 68 30.8 B3R-2-18 B3L-2-18 4' (1219mm) length weight model # lbs. kg (635mm) ← 13" → (330mm) 4-13"→ (330mm) ___ 25"___ (635mm) B4C-2-18 33.6 - 4´(1219mm) ·4´ (1219mm) 4' (1219mm) 33.6 B4I -2-18 74 B4R-2-18 74 33.6 B4L-2-18 B4C-2-18 B4R-2-18 B4L-18 74 33.6 B4R-18 74 33.6 (330mm) 4-13″→ (330mm) 4´ (1219mm) 4´ (1219mm) B4L-18 B4R-18 5' (1524mm) length weight model # lbs. kg ___ 25~__ (635mm) 4 13°-► (330mm) (330mm) B5L-18 80 36.3 (635mm) B5R-18 80 36.3 5 (1524mm) 5´ (1524mm) 5´ (1524mm) B5C-18 80 36.3 B5L-18 B5C-18 B5R-18 6' (1829mm) length weight model # lbs. kg (330mm) 4 13" → (330mm) 4—19″—► (483mm) 4—19"— (483mm) B6C-18 86 39.0 6´ (1829mm) 6' (1829mm) B6C-4-18 86 B6C-18 B6C-4-18 7' (2134mm) length model # lbs. kg —19″ —► (483mm) 4—19″ — (483mm) ___ 25 ___ (635mm) (635mm) B7C-18 92 41.7 7' (2134mm) 7´ (2134mm) B7C-4-18 90 B7C-18 B7C-4-18 8' (2438mm) length weight

8' (2438mm)

B8C-18

(787mm)

__ 31"__ (787mm) ___ 25"___ (635mm)

8' (2438mm)

B8C-4-18