2 Saddleback C	BRONZE WORKS, INC Cove / P.O. Box 1088		Model No. EC-3100		
Travelers F	Rest, SC 29690	REG. #A2601	Item No.		
		ISO #9001			
Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800-	Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800-423-0150 Fax: 864-834-3518 www.tsbrass.com				
This Space for Architect/Engineer Approval	L		ChekPoint*		
Job NameDate	C.				
Model Specified Quantity	ADA Compliant				
Customer/Wholesaler					
Contractor		Rigid Goose w/ 2.2 GPM			
Architect/Engineer	$\overline{\nabla}$		istant Aerator		
[92mm x 106mm x 51 Waterproof Control M w/ Internal Flow Cont AC or DC operated w 24" [610mm] Sensor Cable Removeable Strainer DECK	lodule Box (Blue) rol Setting Switches, // (4) AA Batteries 4 1/8" [105mm] 7 3/8" [185mm] 2 1/4" Max. [57mm] Ø 1" [25mm] Deck Hole		Ø 1/8" [3mm] Ø 1/8" [3mm] Pin installed for Anti-rotation feature. Remove pin if desired. (See Mounting Hole Detail)		
	100-135 VAC Adapte w/ 144" [3658mm] Lo Power Cord. (Remove Rubber Plu on Module and Cable to Connect)	ong ugs e	Mounting Hole Detail Ø1" [25mm] Thru [25mm] (25mm]		
NOTE: Supply Stops by Others 18"	" Compression x 1/2" NPSN ' [457mm] Flex. St. Steel Sເ	upply Hose	∠ø5/32" [4mm]		
Product Specifications: Chrome Plated Brass Deck Mount Rigid Gooseneck w/ VR A Control Module with Internal Flow Con	Aerator, AC/DC trol Setting Switches,	awn Cheo GEF JF :ale:	cked Approved RM JHB Date:		
Temperature Control Mixing Valve, 18 Supply Stop Flexible Connector Hoses	Long Hot & Cold	NTS	09/11/08		
			Sheet: 1 of 2		



(3)

(2)

T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088

Travelers Rest, SC 29690



EC-3100

Model No.

REG. #A2601 Item No.

Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800-423-0150 Fax: 864-834-3518 www.tsbrass.com

(8)

ITEM	SALES	DESCRIPTION	
NO.	NUMBER		
1	B-0199-06	VR Aerator w/ Key	
2	044A	3/8" to Aerator Adapter	
3	006575-45	-015 O-Ring	
4	017195-45	Angled Sensor w/ Cable	
5	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F	
6	016647-45	ChekPoint Electronic Module (Blue)	
7	5EF-0002	A/C Transformer	
8	5EF-0006	Manual Mixing Valve	
9	5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM	
10	Q015425-45	Vandal Resistant Key	
-			

Label for Flow Control Switch Settings is located on Inside of Back Cover.

Flow Control Switches are located inside Module Housing in Black Box next to Battery Compartment. *Switches are set to DEFAULT position: Auto Time Out = 10 seconds Shut Off Delay = 1 second.

Remove (4) screws and back cover to access switches.

(6) Shut Off Delay Selections - 1 sec, 2 sec, 3 sec, 4 sec, 5 sec, 6 sec Product Specifications: Chrome Plated Brass Electronic Faucet: Drawn Approved Checked Deck Mount Rigid Gooseneck w/ VR Aerator, AC/DC GEF JRM JHB Control Module with Internal Flow Control Setting Switches, Scale: Date: Temperature Control Mixing Valve, 18" Long Hot & Cold NTS 09/11/08 Supply Stop Flexible Connector Hoses

*Available Water Flow Control Selections:

9

(6) Auto Time Out Selections - 10 sec, 25 sec, 45 sec, 60 sec, 3 min, 20 min

Sheet: 2 of 2