

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

D	1	
Pro	lect	•
гю	ICCL	

Model # : Item # :

Qty :

Available W/H :

Approval :

Worktop Refrigerator

Worktops Super Deluxe Series

Model : TWR-28SD

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



____ FEATURES & BENEFITS =___

Maintenance-free, Self-Cleaning Condenser (patented) Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The self-cleaning condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe can add a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving Only Turbo Air models

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Efficient refrigeration system

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

High-density CFC free polyurethane insulation

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

Magnetic door gaskets

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

Refrigerator holds 33°F ~ 38°F for the best in food preservation

ISO9001:2008 Intertek Intertek							
Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^\dagger$ (inches)
TWR-28SD	1	7	1	1/4	6.6	175	271/2 x 30 x 331/2

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

Worktop Refrigerator

Model : TWR-28SD

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	6.6			
Compressor HP	1/4			
Cord Length (ft.)	9			
Refrigerant	R-134A			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	7			
Ext. Length Overall (in.)	271/2 (699mm)			
Ext. Depth Overall (in.) *	30 (762mm)			
Ext. Height Overall (in.) ⁺	331/2 (851mm)			
# of Doors	1			
# of Shelves	1			
Net Weight (lbs.)	157			
Gross Weight (lbs.)	175			
Shelf Size (in.)	221/2 x 17			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor **WARRANTY**:

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- 2.5" caster available (optional)
- Legs available (optional)

OPTIONAL ACCESSORIES :

- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- G" ABS plastic leg: 30221M0200
- G" stainless steel leg: 30221M0600
- Additional stainless steel shelf: M277800100
- Door lock: extra lead time will apply, please call factory for more details to order
- External digital thermometer: extra lead time will apply, please call factory for more details to order


(GERMAN


KNIFE



PLAN VIEW

(unit : inch)







Ver.201701

IRapiance



Turbo Air : 800-627-0032 **GK** : 800-500-3519

GREEN WORLD Turbo air

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

